


ABB Motors and Generators		Technical Data Sheet - DOL			
		Project	Location		
Department/Author		Customer name	Customer ref.		Item name 1.00028
Our ref.		Rev/Changed by A	Date of issue 21/11/2017	Saving ident wimes stock.do2.xls	Pages 1(3)
No.	Definition	Data	Unit	Remarks	
1	Product	TEFC, 3-phase, squirrel cage induction motor			
2	Product code	3GBA 082 330-ASD		Calc. ref.	3GZC021008-93
3	Type/Frame	M2BAX 80MC 4			
4	Mounting	IM1001, B3(foot)			
5	Rated output P _N	0.55	kW		
6	Service factor	1			
7	Type of duty	S1(IEC) 100%			
8	Rated voltage U _N	400	VY	± 5 % (IEC 60034-1)	
9	Rated frequency f _N	50	Hz	± 2 % (IEC 60034-1)	
10	Rated speed n _N	1446	r/min		
11	Rated current I _N	1.32	A		
12	No-load current	0.73	A		
13	Starting current I _s /I _N	8.4		Fulfilled IEC 60034-12 design N,H	
14	Nominal torque T _N	3.6	Nm		
15	Locked rotor torque T _s /T _N	2.7			
16	Maximum torque T _{max} /T _N	3.9			
17	Minimum torque T _{min} /T _N	2.7			
18	Speed at minimum torque	150	r/min		
Load characteristics (IEC 60034-2-1:2014)		Load %	Current A	Efficiency %	Power factor
19	PLL determined from residual loss	100	1.32	80.8 / IE3	0.74
20		75	1.1	80.7	0.67
21		50	0.94	78	0.54
22		<i>Start</i>	11.1		0.61
23	Maximum starting time from hot	20	s		
24	Maximum starting time from cold	36	s		
25	Insulation class / Temperature class	F / B			
26	Ambient temperature	40			
27	Altitude	1000	m.a.s.l.		
28	Enclosure	IP55			
29	Cooling system	IC411 self ventilated			
30	Bearing DE/NDE	6204-2Z/C3 - 6203-2Z/C3			
31	Type of Grease				
32	Sound pressure level (LP dB(A) 1m)	48	dB(A)	at load	
33	Moment of inertia J = ¼ GD ²	0.00228	kg-m ²		
34	Balancing				
35	Vibration class				
36	Position of terminal box	Top			
37	Terminal box entries; no, dimens.				
38	Number of power terminals				
39	Direction of rotation	CW or CCW			
40	Weight of rotor	4	kg		
41	Total weight of motor	17	kg		
42	Dimension drawing no.				
43					
44					
45					
Ex-motors					
46					
47					
48					
Option Variant Codes / Definition					
49					
50					
51					
52					
Remarks:					
Data based on situation 22/02/2016					
All data subject to tolerances in accordance with IEC					
Guaranteed values on request					


Project	Location
---------	----------

Department/Author	Customer name	Customer ref.	Item name 1.00028
-------------------	---------------	---------------	-----------------------------

Our ref.	Rev/Changed by	Date of issue	Saving ident	Pages
	A	21/11/2017	wimes stock.do2.xls	2(3)

Product	TEFC, 3-phase, squirrel cage induction motor		
Type/Frame	M2BAX 80MC 4	Calc. ref.	3GZC021008-93
Product code	3GBA 082 330-ASD		
Rated output P _N	0.55	kW	
Type of duty	S1(IEC) 100%		

Voltage (V)	400	Current I _N (A)	1.32	Power factor at P _N	0.74
Frequency (Hz)	50	Speed (r/min)	1446	Efficiency (%) at P _N	80.8



Load characteristics (IEC 60034-2-1:2014)
Data based on situation 22/02/2016


All data subject to tolerances in accordance with IEC



	Project	Location	
Department/Author	Customer name	Customer ref.	Item name 1.00028
Our ref.	Rev/Changed b Date of issue A 21/11/2017	Saving ident wimes stock.do2.xls	Pages 3(3)

Type of product	TEFC, 3-phase, squirrel cage induction motor		
Type/Frame	M2BAX 80MC 4	Calc. ref.	3GZC021008-93
Product code	3GBA 082 330-ASD	Frequency (Hz)	50
Rated output P _N	0.55 kW	Rated current I _N	1.32 A
Type of duty	S1(IEC) 100%		

J _{motor} (kgm ²)	0.0023	Voltage (V) 100%	400	Voltage (V)	400V(100%)
J _{load} (kgm ²)		T _{start} /T _N	2.7	T _{start} /T _N	2.7
Speed (r/min)	1446	Starting time (s)		Starting time (s)	
T _N (Nm)	3.6	Speed (r/min)		Speed (r/min)	
T _{load} (Nm)		I _s /I _n	8.4	I _s /I _n	8.4
Nbr. of Consecutive Starts at UN		T _{max} /T _n	3.9	T _{max} /T _n	3.9



Load characteristics (IEC 60034-2-1:2014)
Data based on situation 22/02/2016

All data subject to tolerances in accordance with IEC